

RV 8-28

Retaining device for heat exchanger cleaning

URACA



URACA GmbH + Co. KG
 P. O. Box 12 60
 D-72563 Bad Urach, Germany
 Telephone ++49 (71 25) 133-0
 Fax ++49 (71 25) 133-202
 www.uraca.com

**Certified
 by LRQA**



RV 8-28
Order no.
W6047-00A

Field of application

- Internal cleaning of pipes/heat exchangers - especially with flexible lances/spirals.
- In 2 directions x/y, free-moving, exact positioning and fixing over the manhole. Distance: 0-900 mm.
- Safety device for the cleaning tool preventing unintended and dangerous exit of the tools out of the protecting pipe (piston effect!)
- Quick and easy clamping or tightening of the device to the heat exchanger flange.
- Drain for the discharge water protecting the service man.


Retaining device required by the German Trade Cooperative Association according to executory provision article 13, para 8 of VBG 87 and test certificate BAU 98078.

| Technical data | RV 8-28 |
|-----------------------|--------------------|
| Pressure range | depending on lance |
| Adaptable lance dia. | 8,5 - 28 mm |
| Operating temperature | max. 70 °C |
| Working radius | 475 mm |
| Weight | 14 kg |

Lance not included in scope of supply.

The multiple URACA programme completes the RV 8-28:

- Flexible lances.
- Rigid lances.
- Suitable rigid and rotating pipe cleaning nozzles.



Adjustable device which can be fixed on the heat exchanger with or without bore holes.